

Codoping double perovskites for singlecomponent white-light-emitting diodes

May 22 2023



Song Hongwei's research team at Jilin University in China developed the new materials. Credit: Song Hongwei's research team at Jilin University in China



developed the new materials.

A new paper published in *Energy Material Advances* explores Eu³⁺-Bi³⁺ codoping double perovskites for single-component white-light-emitting diodes.

"With <u>lead-halide perovskites</u> reaching a mature research stage approaching product marketing, concerns remain about the materials' stability and the toxicity of lead-based salts," said paper author Hongwei Song, professor at College of Electronic Science and Engineering, Jilin University.

Double perovskites with $Cs_2AgInCl_6$ composition, often doped with various elements, have been in the spotlight owing to their intriguing optical properties, namely, self-trapped exciton (STEs) emission and dopant-induced photoluminescence. This interest has sparked different synthesis approaches towards both crystals and nanocrystals, and the exploration of many alloy compositions with mono- and trivalent cations other than Ag^+ and In^{3+} .

Song explained that, in the development of lead-free perovskite materials, people's first thought is to replace Pb element with a non-toxic element. In order to replace Pb in halide perovskite, researchers chose several low-toxic cations in the same period closest to it, such as Sn, Ge, Bi, Sb, In, etc., because they have a similar inactive shell s orbital.

This is the key to the unique photoelectric properties of perovskite materials. Lead-based perovskite materials have attracted great attentions in solid-state lighting area due to their high efficiency, high color rendering and tunable luminescence performance. This is both an opportunity and a challenge for the overall development of the



photoelectric industry.

"Since the pioneering work on $Cs_2AgInCl_6$ in 2017 reported by Giustino et al. and Zhou et al. nearly simultaneously, many efforts have been devoted to its synthesis, modification of its composition, study of its electronic structure, optoelectronic properties, and applications. Recently, a record of white light emission with 86 % PLQY was achieved by Luo et al. via simultaneous alloying of Ag⁺ with Na⁺ and Bi³⁺ doping, marking an important milestone in the development of $Cs_2AgInCl_6$ related materials," Song said.

"Despite several advantages, major issues with these lead halide perovskites remain their poor stability and toxicity. In order to solve such problems, various attempts have been made to reduce the toxicity of perovskites while still maintaining their efficient optical properties."

The existence of Bi^{3+} ions decrease the excitation (absorption) energy, provides a new absorption channel and increases the energy transfer rate to Eu³⁺ ions. Through adjusting the Bi³⁺ and Eu³⁺ concentrations, a maximum photoluminescence efficiency (PLQY) of 80.1% is obtained in 6% Eu³⁺ and 0.5% Bi³⁺ co-doped Cs₂AgInCl₆ DPs.

"The energy transfer efficiency can be fitted with the decay rates under different Bi^{3+} doping concentrations. It can be seen that the energy transfer rate improves as a whole with the increase of the doping concentration of Bi^{3+} , and the optimum energy transfer rate corresponding to the Bi^{3+} concentration is 0.5%. Next, we conducted PLQY test on the materials. For the undoped Cs₂AgInCl₆ DPs, PLQY is only 0.5%, which dramatically increases to 20.1% after the addition of Bi^{3+} . After [being] co-doped with Eu^{3+} and Bi^{3+} ions, PLQY continues to increase, and reaches the maximum of 80.1% when the Eu concentration reaches 6%," Song said.



"Here, we propose a possible mechanism to describe Eu^{3+} emission in Bi/Eu3+: $Cs_2AgInCl_6$. $Cs_2AgInCl_6$ DP is a direct bandgap semiconductor. Bi³⁺ doping provides a new absorption channel for the material, which may be caused by the contribution of the Bi³⁺ orbital in the band edge, breaking the STE-state compatibility ban transition, generating a new light absorption channel at a lower energy, and promoting the PLQY emitted by STE. For the Eu³⁺emission, we think there are two pathways. First, the energy transfer from STE to Eu³⁺ ions is possible as we have observed the Eu³⁺ emission in the Eu³⁺ doped Cs2AgInCl6 DPs. Second, the Eu³⁺ emission may mainly come from the energy transfer from Bi³⁺ ions to Eu³⁺ ions. The Bi³⁺ ions absorb the excitation light and transfer the energy from ¹P₁, ³P₂, ³P₁, ³P₀ levels of Bi³⁺ ions to ⁵D₃, ⁵D₂, ⁵D₁ and ⁵D₀ levels of Eu³⁺ ions. The characteristic emission of Eu³⁺ ions is then formed through ⁵D₀ \rightarrow ⁷F_j(j=0,1,2,3) transitions."

"Finally, we prepared the white light emitting diodes based on Bi^{3+} and Eu^{3+} codoped $Cs_2AgInCl_6$ DPs were fabricated with the optimum color rendering index of 89, the optimal luminous efficiency of 88.1 lm/W and a half-lifetime of 1493 h. This strategy of imparting optical functions to metal halide DPs may lead to future applications, such as optical fiber communications, daily lighting, military industry, displays, and other fields," Song said.

More information: Tianyuan Wang et al, Eu³⁺-Bi³⁺ Codoping Double Perovskites for Single-Component White-Light-Emitting Diodes, *Energy Material Advances* (2023). DOI: 10.34133/energymatadv.0024

Provided by Beijing Institute of Technology Press Co., Ltd

Citation: Codoping double perovskites for single-component white-light-emitting diodes (2023,



May 22) retrieved 6 May 2024 from <u>https://phys.org/news/2023-05-codoping-perovskites-single-component-white-light-emitting-diodes.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.