

A new generation of spaceplanes is taking advantage of the latest in technology

February 8 2024, by Oluwamayokun Adetoro and James Campbell



Dream Chaser would ferry cargo, and eventually crew, to low-Earth orbit.
Credit: Ken Ulbrich / NASA

[NASA's space shuttle](#) operated in low-Earth orbit for 30 years before its retirement in 2011. However, the US space agency's [replacement for this vehicle, Orion](#), returned to the conical capsule design familiar from the Apollo missions. This was because NASA intended that this newer craft be used for exploring targets in deep space, such as the moon.

But in recent years, we have seen a return of the [spaceplane](#) design. [Since 2010](#), the US Space Force (and formerly the US Air Force) has been [launching a robotic spaceplane called the X-37B](#) into low Earth orbit on classified missions. China has its own [military spaceplane called Shenlong](#).

This year could see a test flight of the company Sierra Space's [Dream Chaser](#)—the first commercial spaceplane capable of orbital flight. If all goes well, the [vehicle](#) could be used to resupply the International Space Station (ISS) with cargo and, eventually, crew.

Spaceplanes can fly or glide in the Earth's atmosphere and land on runways rather than using parachutes to land in water or flat ground like capsules. They're also more maneuverable as the spacecraft reenters the atmosphere, increasing the area of the Earth's surface where landing is possible from a specific re-entry point.

Spaceplanes also allow a gentler but longer flight path during re-entry and a softer landing, which is easier on crew and cargo than capsules, which can land with a thump. A runway also allows ground support crews and infrastructure to be ready at the landing location.

Cost and complexity



The US Space Force's X-37B carries no crew, and its missions are classified.
Credit: Staff Sgt. Adam Shanks / US Space Force

But spaceplanes are more complex and heavier than an equivalent capsule. The winged body shape poses a particular challenge for designing thermal protection systems (TPS)—the heat-resistant materials that protect the craft from scorching temperatures on re-entry. These [additional costs](#) mean it's impractical to design a spaceplane for a single flight. They need to be used again and again to be viable.

There has been interest in spaceplanes from the earliest days of human spaceflight. A military spaceplane project called [Dyna-Soar](#) was started in the US in 1957, then canceled just after construction started. The vehicle was sophisticated for its time, built using a metal alloy that is

able to withstand high temperatures and featuring a heat shield on the front that could be detached after it returned from space, so that the pilot could see clearly as he was landing.

The [space shuttle](#), which entered service in 1981, was the first operational spaceplane. It was supposed to launch more often than it did and have [greater reusability](#) but it turned out that extensive refurbishment was required between launches. It did, however, demonstrate the ability to return astronauts and large cargo from orbit.

Other space agencies invested in the 1980s and 1990s, in Europe, with [the Hermes spaceplane](#), and Japan, with [the HOPE vehicle](#). Both programs were canceled in large part because of cost. The Soviet Union developed its own [shuttle-like vehicle called Buran](#), which successfully flew to space once in 1988. The program was canceled after the collapse of the Soviet Union.

Feeling the heat

Spaceplanes have specific requirements for the final part of their journeys—as they return from space. [During atmospheric re-entry](#), they are heated to over one thousand degrees Celsius as they travel at hypersonic speeds of over seven kilometers per second—more than 20 times the speed of sound. A blunt nose design (where the edge of the spacecraft is rounded) is an ideal shape because it reduces build-up of heat at the foremost part of the vehicle.



On launch, the space shuttle was attached to the side of a large external propellant tank. Credit: NASA / JSC

Even so, the expected temperatures experienced by the craft can still be as high as 1600°C , necessitating a thermal protection system on the outside of the vehicle. [The space shuttle TPS](#) included ceramic tiles that were especially heat resistant and a reinforced carbon-carbon matrix that was capable of withstanding temperatures as high as 2400°C .

The [loss of the Columbia shuttle](#) during re-entry in 2003, causing the deaths of seven astronauts, was the result of a breach in the TPS on the leading edge of the wing. This resulted from a piece of insulating foam flying off the shuttle's external tank during Columbia's launch and hitting the wing.

This foam issue was recurrent with the shuttle because of the way it launched on the side of the external propellant tank. But newer spaceplane designs will fly atop conventional rockets, where falling foam isn't a problem.

An effective TPS remains vital for the [future success of spaceplanes](#), as are systems that monitor the TPS performance in real time.

Current vehicles

There are currently two operating spaceplanes, one Chinese and one American, that can reach orbit. Little information is available on China's Shenlong, but [the US military's X-37B](#) is better known. Weighing close to five tons at launch, the nine meter-long, uncrewed vehicle is launched using a conventional rocket and lands autonomously on a runway at the end of its mission.



Dream Chaser undergoing evaluation at Nasa's Neil Armstrong Test Facility.
Credit: NASA

The X-37B's TPS uses tiles similar to the shuttle over the lower surface with a lower-cost alternative to reinforced [carbon-carbon](#) called Tufroc, developed for the X37B, on the nose and leading edges.

They should soon be joined by Dream Chaser, which was developed by the company to carry both cargo and astronauts, but NASA wants to prove its safety before carrying people by using it to carry cargo to the space station first. The ability to return comparatively fragile cargo to the surface because of a softer landing is a key capability. The tiles that protect Dream Chaser are made from silica, and [each has a unique shape](#) matched to the area on the vehicle they are designed to protect.

Future developments

There is continued interest in spaceplanes because of their ability to return crew and cargo to a runway. The demand for this capability is limited now. But if the costs of launching to space continue falling and an expansion of industry in space raises demand, they will become an increasingly viable alternative to capsules.

Longer term, there is also potential for spaceplanes capable of reaching orbit after taking off from a runway. The challenges of developing these single-stage-to-orbit (SSTO) vehicles is considerable. However, [concepts such as the Skylon vehicle](#) are leading to technical developments that could eventually support development of an SSTO craft.

For the foreseeable future, spaceplanes look promising for the following reasons: new design techniques, improved materials for the TPS, advanced computer modeling and simulation tools for optimizing different aspects of design and flight parameters and continuous improvements in propulsion systems.

Given that several governments, space agencies, and private companies worldwide are investing heavily in spaceplane research and development, we could see a future where flights with these vehicles become routine.

This article is republished from [The Conversation](#) under a Creative Commons license. Read the [original article](#).

Provided by The Conversation

Citation: A new generation of spaceplanes is taking advantage of the latest in technology (2024, February 8) retrieved 28 April 2024 from <https://phys.org/news/2024-02-generation-spaceplanes-advantage-latest-technology.html>

<p>This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.</p>
--