

Study sheds light on CO₂ absorption mechanism of cement-based materials



Credit: *The Journal of Physical Chemistry C* (2024). DOI: 10.1021/acs.jpcc.4c01714

Carbon dioxide (CO_2) emissions are currently one of the leading causes of global warming. Cement-based materials have shown promising applications in capturing and solidifying CO_2 as minerals through a process called carbonation, offering a potential solution to mitigate the challenges associated with climate change. Consequently, numerous studies have been conducted on the carbonation of cement-based



materials to improve the efficiency of carbonation.

Put simply, carbonation in cement paste involves the dissolution of CO_2 in water, followed by interaction with calcium silicate hydrates (C–S–H), formed during the hydration of raw materials. During this reaction, the dissolved CO_2 forms carbonate ions ($CO_3^{2^-}$), and further reacts with calcium ions (Ca^{2^+}) from C–S–H to create calcium carbonate precipitates. However, despite extensive studies with varying parameters, the complete explanation of carbonation mechanisms is not clearly understood due to the unstable nature of cement paste compounds.

Previous studies have shown that carbonation is strongly impacted by relative humidity (RH), CO_2 solubility, calcium/silicate (Ca/Si) ratio, and concentration and saturation level of water in C–S–H. Moreover, it is also important to understand the influence of ions and water transport through the nanometer-sized pores in C–S–H layers, known as gel-pore water.

To answer these questions, Associate Professor Takahiro Ohkubo from the Graduate School of Engineering at Chiba University with his team of researchers, including Taiki Uno from Chiba University, Professor Ippei Maruyama and Naohiko Saeki from The University of Tokyo, Associate Professor Yuya Suda from University of Ryukyus, Atsushi Teramoto from Hiroshima University, and Professor Ryoma Kitagaki from Hokkaido University investigated the mechanism of carbonation reaction under different Ca/Si ratios and RH conditions.

Their study was <u>published</u> in *The Journal of Physical Chemistry C* on July 8, 2024.

"The role of water transport and carbonation-related structural changes remains an open question. In this study we used a new method to study these factors, using ²⁹Si <u>nuclear magnetic resonance</u> (NMR) and ¹H



NMR relaxometry, which has been established as an ideal tool for studying <u>water transport</u> in C–S–H," says Associate Professor Ohkubo.

To study the carbonation process, the researchers synthesized C–S–H and subjected them to accelerated carbonation using 100% CO₂, far higher than atmospheric levels.

"Natural carbonation in cement materials occurs over several decades by absorbing atmospheric CO_2 , making it difficult to study in a lab setting. Accelerated carbonation experiments with elevated CO_2 concentrations provide a practical solution to this challenge," explains Associate Professor Ohkubo.

The samples were synthesized under varying RH conditions and Ca/Si ratios. Further, they studied the C–S–H samples using ²⁹Si NMR, and the water exchange processes using ¹H NMR relaxometry under a deuterium dioxide (D_2O) atmosphere.

The researchers found that the structural changes induced by the carbonation reaction, including the collapse of the C–S–H chain structure and changes in the <u>pore size</u> were heavily influenced by the Ca/Si ratio of the C–S–H chain and RH conditions. Additionally, lower RH conditions and a high Ca/Si ratio resulted in smaller-sized pores, suppressing the leaching of Ca²⁺ ions and water from the interlayer space to gel-pores, leading to inefficient carbonation.

"Our study shows that the carbonation process occurs due to a combination of structural modifications and <u>mass transfer</u>, signifying the importance of studying their interplay, rather than just structural changes," says Associate Professor Ohkubo.

Further highlighting the implications of the present study, Associate Professor Ohkubo adds, "Our findings can contribute to developing new



building materials that can absorb large amounts of atmospheric CO_2 . Additionally, carbonation reactions are also common in <u>organic matter</u> and hence, our new approach will also help to understand the carbonation of compounds in the natural environment."

In conclusion, this study sheds light on the carbonation reaction of cement-based materials, offering a potential solution to CO_2 reduction.

More information: Taiki Uno et al, Understanding the Carbonation Phenomenon of C–S–H through Layer Structure Changes and Water Exchange, *The Journal of Physical Chemistry C* (2024). DOI: <u>10.1021/acs.jpcc.4c01714</u>

Provided by Chiba University

Citation: Study sheds light on CO₂ absorption mechanism of cement-based materials (2024, September 9) retrieved 9 September 2024 from <u>https://phys.org/news/2024-09-absorption-mechanism-cement-based-materials.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.