

A quiet phase: NIST optical tools produce ultra-low-noise microwave signals

June 27 2011



Matt Kirchner, a University of Colorado graduate student, fine-tunes an ultra-stable microwave generator that he helps operate at NIST. Credit: Burrus/NIST

By combining advanced laser technologies in a new way, physicists at the National Institute of Standards and Technology (NIST) have generated microwave signals that are more pure and stable than those from conventional electronic sources. The apparatus could improve signal stability and resolution in radar, communications and navigation systems, and certain types of atomic clocks.

Described in [Nature Photonics](#), NIST's low-noise apparatus is a new application of [optical frequency](#) combs, tools based on ultrafast lasers for precisely measuring [optical frequencies](#), or colors, of light. Frequency combs are best known as the "gears" for experimental next-generation atomic clocks, where they convert [optical signals](#) to lower

microwave frequencies, which can be counted electronically.

The new low-noise system is so good that NIST scientists actually had to make two copies of the apparatus just to have a separate tool precise enough to measure the system's performance. Each system is based on a continuous-wave laser with its frequency locked to the extremely stable length of an [optical cavity](#) with a high "quality factor," assuring a steady and persistent signal. This laser, which emitted yellow light in the demonstration but could be another color, is connected to a frequency comb that transfers the high level of stability to microwaves. The transfer process greatly reduces—to one-thousandth of the previous level—random fluctuations in the peaks and valleys, or phase, of the electromagnetic waves over time scales of a second or less. This results in a stronger, purer signal at the exact desired frequency.

The base microwave signal is 1 gigahertz (GHz, or 1 billion cycles per second), which is the repetition rate of the ultrafast laser pulses that generate the frequency comb. The signal can also be a harmonic, or multiple, of that frequency. The laser illuminates a photodiode that produces a signal at 1 GHz or any multiple up to about 15 GHz. For example, many common radar systems use signals near 10 GHz.

NIST's low-noise oscillator might be useful in radar systems for detecting faint or slow-moving objects. The system might also be used to make [atomic clocks](#) operating at [microwave frequencies](#), such as the current international standard cesium atom clocks, , more stable. Other applications could include high-resolution analog-to-digital conversion of very fast signals, such as for communications or navigation, and radio astronomy that couples signals from space with arrival times at multiple antennas.

More information: T.M. Fortier, M.S. Kirchner, F. Quinlan, J. Taylor, J.C. Bergquist, T. Rosenband, N. Lemke, A. Ludlow, Y. Jiang, C.W.

Oates and S.A. Diddams. Generation of ultrastable microwaves via optical frequency division. *Nature Photonics*. Published online June 26, 2011.

Provided by National Institute of Standards and Technology

Citation: A quiet phase: NIST optical tools produce ultra-low-noise microwave signals (2011, June 27) retrieved 24 April 2024 from <https://phys.org/news/2011-06-quiet-phase-nist-optical-tools.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.