

Superconductors for efficient wind power plants: Researchers develop cooling system for novel generator

4 January 2013



Superconducting generators will provide offshore wind power plants with higher performance at lower costs. Credit: Tecnalía

(Phys.org)—An efficient, robust, and compact wind power plant with a 10 MW superconducting generator is being developed by partners from industry and science within the recently established EU project SUPRAPOWER. Superconduction enables considerable savings of energy and raw materials. Within SUPRAPOWER, researchers at KIT's Institute for Technical Physics (ITEP) develop a rotating cryostat cooling the superconducting coils down to minus 253°C - a temperature crucial for electric current flow without resistance.

Wind power will make a major contribution to the energy turnaround. Efficient [power generation](#) by means of offshore power plants requires powerful, reliable generators that do not cause disproportionately high logistic efforts and do not require complex foundations. Using generators with [superconductors](#), performance can be

increased to 10 MW while at the same time reducing the units' weights and sizes. Besides, superconducting generators can be built with less than one hundredth of the quantity of [rare earths](#) required for manufacturing the currently most frequently used permanent magnet generator. Superconduction, hence, allows setting up of efficient, robust, and compact [wind power plants](#) at reduced building, operating, and maintenance costs.

It is the objective of the EU-supported project SUPRAPOWER (SUPERconducting, Reliable, lightweight, And more POWERful offshore wind turbine) to use the high potential of supraconduction for expansion of wind power. In the four-year project that has started now nine partners from industry and science cooperate under the coordination of Fundación Tecnalía Research & Innovation, Spain. Together, the partners develop a wind power plant with direct-drive superconducting generator. The innovative direct drive, in addition, reduces transport and maintenance costs and extends the service life of the turbine.

The Cryogenic Engineering Division at KIT's Institute for Technical Physics (ITEP) contributes the cooling system: Below a certain temperature, superconductors have no electrical resistance and conduct electricity without loss. To ensure proper operation of the superconducting generator, the coils must be cooled below this so-called transition temperature. The researchers at ITEP are developing a rotating low-loss [cryostat](#) that cools down the superconducting coils to 20 Kelvin (minus 253.15 °C) through pure heat conduction by means of small Gifford-McMahon coolers provided by the project partner Oerlikon Leybold Vacuum. "Since the cooling performance of such coolers is limited, we must ensure that heat between them and the superconducting coils is conducted well. Besides,

we must consider the influence of rotation on the heat pipes we may use. On the other hand, the cryostat needs a highly effective thermal insulation," explains Head of the Cryogenic Engineering Division Dr. Holger Neumann. Work on the cooling system translates the findings from fundamental research to practice and, hence, is most attractive to young scientists.

Provided by Karlsruhe Institute of Technology

APA citation: Superconductors for efficient wind power plants: Researchers develop cooling system for novel generator (2013, January 4) retrieved 24 September 2021 from <https://phys.org/news/2013-01-superconductors-efficient-power-cooling.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.