

Researchers find way of developing composites that self-heal at very low temperatures

13 September 2016

Scientists have developed a method of allowing materials, commonly used in aircraft and satellites, to self-heal cracks at temperatures well below freezing.

The paper, published in *Royal Society Open Science*, is the first to show that [self-healing materials](#) can be manipulated to operate at very [low temperatures](#) (-60°C).

The team, led by the University of Birmingham (UK) and Harbin Institute of Technology (China), state that it could be applied to fibre-reinforced materials used in situations where repair or replacement is challenging such as [offshore wind turbines](#), or even 'impossible', such as [aircraft](#) and satellites during flight.

Self-[healing](#) composites are able to restore their properties automatically, when needing repair. In favourable conditions, composites have yielded impressive healing efficiencies. Indeed, previous research efforts have resulted in healing efficiencies above 100%, indicating that the function or performance of the healed material can be better than that prior to damage.

However, until this paper, healing was deemed insufficient in adverse conditions, such as very low temperature.

Similarly to how some animals in the natural world maintain a constant body temperature to keep enzymes active, the new structural composite maintains its core temperature.

Three-dimensional hollow vessels, with the purpose of delivering and releasing the healing agents, and a porous conductive element, to provide internal heating and to defrost where needed, are embedded in the composite.

Yongjing Wang, PhD student at the University of Birmingham, explained, "Both of the elements are essential. Without the heating element, the liquid would be frozen at -60°C and the chemical reaction cannot be triggered. Without the vessels, the healing liquid cannot be automatically delivered to the cracks."

A healing efficiency of over 100% at temperatures of -60°C was obtained in a glass fibre-reinforced laminate, but the technique could be applied across a majority of self-healing composites.

Tests were run using a copper foam sheet or a carbon nanotube sheet as the conductive layer. The latter of the two was able to self-heal more effectively with an average recovery of 107.7% in fracture energy and 96.22% in peak load.

The healed fibre-reinforced composite, or host material, would therefore have higher interlaminar properties - that is the bonding quality between layers. The higher those properties, the less likely it is that cracks will occur in the future.

Mr Wang added, "Fibre-reinforced composites are popular due to them being both strong and lightweight, ideal for aircraft or satellites, but the risk of internal micro-cracks can cause catastrophic failure. These [cracks](#) are not only hard to detect, but also to [repair](#), hence the need for the ability to self-heal."

The group will now look to eliminate the negative effects that heating elements have on peak load by using a more advanced heating layer. Their ultimate goal, however, is to develop new healing mechanisms for more composites that can recover effectively regardless the size of faults in any condition.

More information: Sustainable Self-healing at Ultra-low Temperatures in Structural Composites Incorporating Hollow Vessels and Heating Elements, *Royal Society Open Science*, [rsos.royalsocietypublishing.or ... /10.1098/rsos.160488](https://royalsocietypublishing.org/doi/10.1098/rsos.160488)

Provided by University of Birmingham

APA citation: Researchers find way of developing composites that self-heal at very low temperatures (2016, September 13) retrieved 21 September 2019 from <https://phys.org/news/2016-09-composites-self-heal-temperatures.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.