

SimRadar: A polarimetric radar time-series simulator for tornadic debris studies

May 1 2017



A University of Oklahoma research team with the Advanced Radar Research Center has developed the first numerical polarimetric radar simulator to study and characterize scattering mechanisms of debris particles in tornadoes. Credit: University of Oklahoma

A University of Oklahoma research team with the Advanced Radar

Research Center has developed the first numerical polarimetric radar simulator to study and characterize scattering mechanisms of debris particles in tornadoes. Characterizing the debris field of a tornado is vital given flying debris cause most tornado fatalities. Tornado debris characteristics are poorly understood even though the upgrade of the nation's radar network to dual polarimetric radar offers potentially valuable capabilities for improving tornado warnings and nowcasting.

"These results are important for operational weather forecasters and emergency managers," says Nick Anderson, program director in the National Science Foundation Division of Atmospheric and Geospace Sciences, which funded the research. "An improved understanding of what weather radars tell us about tornado debris can help provide more accurate [tornado warnings](#), and quickly direct emergency personnel to affected areas."

"With this simulator, we can explain in great detail to the operational weather community the tornadic echo from the polarimetric [radar](#)," said Robert Palmer, ARRC executive director. "The signal received by the dual polarimetric radar is not easily understood because rain is mixed with the debris. The knowledge we gain from this study will improve tornado detection and near real-time damage estimation."

Numerous controlled anechoic chamber measurements of tornadic debris were conducted at the Radar Innovations Laboratory on the OU Research Campus to determine the scattering characteristics of several debris types—leaves, shingles and boards. Palmer, D.J. Bodine, B.L. Cheong, C.J. Fulton and S.M. Torres, the center, and the OU Schools of Electrical and Computer Engineering and Meteorology, developed the simulator to provide comparisons for actual polarimetric radar measurements.

Before this study, there were many unanswered questions related to

tornado debris scattering, such as knowing how the size, concentration and shape of different debris types affect polarimetric variables. How the radar identifies the debris is equally as important. Orientation of debris makes a difference as well as how the debris falls through the atmosphere. Overall, understanding debris scattering characteristics aid in the discovery of the relationship between debris characteristics, such as lofting and centrifuging, and tornado dynamics.

OU team members were responsible for various aspects of this study. Coordination of damage surveys and collection of [debris](#) samples were led by Bodine. Field experiments were designed by team members in collaboration with Howard Bluestein, OU School of Meteorology. Electromagnetic simulations and anechoic chamber experiments were led by Fulton. The signal processing algorithms were developed by Torres and his team. Cheong led the simulation development team.

More information: Boon Leng Cheong et al, SimRadar: A Polarimetric Radar Time-Series Simulator for Tornadic Debris Studies, *IEEE Transactions on Geoscience and Remote Sensing* (2017). [DOI: 10.1109/TGRS.2017.2655363](#)

Provided by University of Oklahoma

Citation: SimRadar: A polarimetric radar time-series simulator for tornadic debris studies (2017, May 1) retrieved 19 April 2024 from <https://phys.org/news/2017-05-simradar-polarimetric-radar-time-series-simulator.html>

<p>This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.</p>
--