


The stacked color sensor

16 November 2017, by Karin Weinmann



Original image (left) and corresponding portrayal of the red, green and blue regions, and a composite image. Credit: Empa

Red-sensitive, blue-sensitive and green-sensitive color sensors stacked on top of each other instead of being lined up in a mosaic pattern – this principle could allow image sensors with unprecedented resolution and sensitivity to light to be created. However, so far, the reality hasn't quite met expectations. Researchers from Empa and ETH Zurich have now developed a sensor prototype that absorbs light almost optimally – and is also cheap to produce.

The human eye has three different types of sensory cells for the perception of [colour](#): cells that are respectively sensitive to red, green and blue alternate in the eye and combine their information to create an overall coloured image. Image [sensors](#), for example in mobile phone cameras, work in a similar way: blue, green and red sensors alternate in a mosaic-like pattern. Intelligent software algorithms calculate a high-resolution colour image from the individual colour pixels.


However, the principle also has some inherent limitations: as each individual pixel can only absorb a small part of the light spectrum that hits it, a large part of the light is lost. In addition, the sensors have basically reached the limits of miniaturisation,

and unwanted image disturbances can occur; these are known as colour moiré effects and have to be laboriously removed from the finished image.

Transparent only for certain colours

Researchers have therefore been working for a number of years on the idea of stacking the three sensors instead of placing them next to each other. Of course, this requires that the sensors on top let through the light frequencies that they do not absorb to the sensors underneath. At the end of the 1990s, this type of sensor was successfully produced for the first time. It consisted of three stacked silicon layers, each of which absorbed only one colour.

This actually resulted in a commercially available image sensor. However, this was not successful on the market because the [absorption spectra](#) of the different layers were not distinct enough, so part of the green and red light was absorbed by the blue-sensitive layer. The colours therefore blurred and the light sensitivity was thus lower than for ordinary light sensors. In addition, the production of the absorbing silicon layers required a complex and expensive manufacturing process.



Stack instead of mosaic: the perovskite layers each absorb only part of the light spectrum. Credit: Empa

dissipative internal optical filtering with solution-grown perovskite single crystals for full-colour imaging, *NPG Asia Materials* (2017). [DOI: 10.1038/am.2017.163](https://doi.org/10.1038/am.2017.163)

Empa researchers have now succeeded in developing a sensor prototype that circumvents these problems. It consists of three different types of perovskites - a semiconducting material that has become increasingly important during the last few years, for example in the development of new solar cells, due to its outstanding electrical properties and good optical absorption capacity. Depending on the composition of these perovskites, they can, for example, absorb part of the light spectrum, but remain transparent for the rest of the spectrum. The researchers in Maksym Kovalenko's group at Empa and ETH Zurich used this principle to create a colour sensor with a size of just one pixel. The researchers were able to reproduce both simple one-dimensional and more realistic two-dimensional images with an extremely high colour fidelity.

Provided by Swiss Federal Laboratories for Materials Science and Technology

Accurate recognition of colours

The advantages of this new approach are clear: the absorption spectra are clearly differentiated and the colour recognition is thus much more precise than with silicon. In addition, the absorption coefficients, especially for the [light](#) components with higher wavelengths (green and red), are considerably higher in the perovskites than in silicon. As a result, the layers can be made significantly smaller, which in turn allows smaller [pixel](#) sizes. This is not crucial in the case of ordinary camera sensors; however, for other analysis technologies, such as spectroscopy, this could permit significantly higher spatial resolution. The perovskites can also be produced using a comparatively cheap process.

However, more work is still needed in order to further develop this prototype into a commercially usable image sensor. Key areas include the miniaturisation of pixels and the development of methods for producing an entire matrix of such pixels in one step. According to Kovalenko, this should be possible with existing technologies.

More information: Sergii Yakunin et al, Non-

APA citation: The stacked color sensor (2017, November 16) retrieved 25 November 2020 from <https://phys.org/news/2017-11-stacked-sensor.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.