

New approach offers high-resolution seismic monitoring of the shallow subsurface

October 1 2018



Credit: CC0 Public Domain

Scientists have long sought accurate monitoring of seismic activity to identify natural phenomena such as earthquakes, volcanic eruptions and the leakage of fluids stored deep underground. Time-lapse four-dimensional seismic monitoring surveys that employ an active seismic source can accurately map the subsurface, and comparing results from different surveys can show how fluids such as CO₂ move in deep geological reservoirs. However, the expense of such surveys limits how often data can be gathered, meaning that subsequent analysis often has poor temporal resolution. An alternative that provides a continuous dataset is the passive monitoring of ambient seismic noise, but the accuracy of this approach depends on the ambient sources, which can change over time.

In an article recently published in *Geophysics*, a team of researchers from Kyushu University and industrial and governmental representatives from Japan and Canada report a new method for accurately monitoring the shallow subsurface at a high spatiotemporal resolution. The method was developed using data from 2014 to 2016 that was collected by the Accurately Controlled Routinely Operated Signal System (ACROSS) located at the Aquistore CO₂ storage site in Saskatchewan, Canada.

Obtaining a high-resolution characterization of the shallow subsurface has previously been limited by the number of ACROSS units. The researchers have now overcome this obstacle. Lead author Tatsunori Ikeda says, "Applying spatially windowed surface-wave analysis allowed us to study the spatial variation of surface wave velocities using data from a single ACROSS unit."

The research team validated their method against data gathered from hundreds of geophone measuring devices located around the ACROSS unit and a computational model of the site. Their analysis of the surface waves shows spatial variation in the surface wave velocities, and the impact of seasonal weather on these velocities. Confirmation of the method's accuracy highlights its potential to identify changes in the shallow subsurface that may be caused by [natural phenomena](#) or fluids leaking from storage sites much deeper underground.

As well as drawing together experts from a variety of organizations in Japan and Canada, the publication represents another step forward for researchers in Kyushu University's International Institute for Carbon-Neutral Energy Research (I2CNER). Co-author Takeshi Tsuji says, "The approach contributes to our ongoing work in Kyushu University to develop a downsized, continuous and controlled seismic monitoring system." The researchers have been operating the downsized [monitoring](#) system at the Kuju geothermal and volcanological research station on Japan's Kyushu Island.

More information: Tatsunori Ikeda et al. Imaging And Monitoring Of The Shallow Subsurface Using Spatially Windowed Surface-Wave Analysis With A Single Permanent Seismic Source, *Geophysics* (2018). [DOI: 10.1190/GEO2018-0084.1](https://doi.org/10.1190/GEO2018-0084.1)

Provided by Kyushu University

Citation: New approach offers high-resolution seismic monitoring of the shallow subsurface (2018, October 1) retrieved 19 September 2024 from <https://phys.org/news/2018-10-approach-high-resolution-seismic-shallow-subsurface.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private

study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.