

Scientists propose data encoding method for the 6G standard

June 12 2020



Credit: CC0 Public Domain

Researchers around the world are working on methods to transfer data in the terahertz (THz) range, which would make it possible to send and receive information more quickly than today's technology. But it is much

more difficult to encode data in the THz range than in the GHz range currently used by 5G technology. A group of scientists from ITMO University has demonstrated the possibility of modifying terahertz pulses in order to use them for data transmission. They have published their results in *Scientific Reports*.

Telecommunications companies in [advanced economies](#) are beginning to adopt the new 5G standard, which will provide previously impossible wireless data transfer speeds. Meanwhile, as companies roll out this new generation of data networks, scientists are already at work on its successor. "We're talking about 6G technologies," says Egor Oparin, a staff member of ITMO University's Laboratory of Femtosecond Optics and Femtotechnologies. "They will increase data transfer speeds by anywhere from 100 to 1,000 times, but implementing them will require us to switch to the terahertz range."

Today, a technology for simultaneous transfer of multiple data channels over a single physical channel has been successfully implemented in the infrared (IR) range. This technology is based on the interaction between two broadband IR pulses with a bandwidth measured in tens of nanometers. In the terahertz range, the bandwidth of such pulses would be much larger—and so, in turn, would be their capacity for data transfer.

But scientists and engineers will need to find solutions to numerous crucial issues. One such issue has to do with ensuring the interference of two pulses, which would result in a so-called [pulse](#) train, or frequency comb, used to encode data.



Egor Oparin, a staff member of ITMO University's Laboratory of Femtosecond Optics and Femtotechnologies. Credit: Egor Oparin

"In the terahertz range, pulses tend to contain a small number of field oscillations; literally one or two per pulse," says Egor Oparin. "They are very short and look like thin peaks on a graph. It is quite challenging to achieve interference between such pulses, as they are difficult to overlap."

A team of scientists at ITMO University has suggested extending the pulse in time so that it would last several times longer but still be measured in picoseconds. In this case, the frequencies within a pulse would not occur simultaneously, but follow one another in succession. In scientific terms, this is referred to as chirping, or linear-frequency

modulation. However, this presents another challenge: Although chirping technologies are quite well developed in the infrared range, there is a lack of research on the technique's use in the terahertz range.

"We've turned to the technologies used in the microwave range," says Egor Oparin, who is a co-author of the paper.

"They actively employ metal waveguides, which tend to have high dispersion, meaning that different emission frequencies propagate at different speeds there. But in the microwave range, these waveguides are used in single mode, or, to put it differently, the field is distributed in one configuration, a specific, narrow frequency band, and as a rule, in one wavelength. We took a similar waveguide of a size suitable for the terahertz range and passed a broadband signal through it so that it would propagate in different configurations. Because of this, the pulse became longer in duration, changing from two to about seven picoseconds, which is three and a half times more. This became our solution."

By using a waveguide, researchers have been able to increase the length of the pulses to a duration that is necessary from a theoretical standpoint. This made it possible to achieve interference between two chirped pulses that together create a pulse train. "What's great about this pulse train is that it exhibits a dependence between a pulse's structure in time and the spectrum," says Oparin. "So we have temporal form, or simply put, field oscillations in time, and spectral form, which represents those oscillations in the frequency domain. Let's say we've got three peaks, three substructures in the temporal form, and three corresponding substructures in the spectral form. By using a special filter to remove parts of the spectral form, we can 'blink' in the temporal form and the other way around. This could be the basis for data encoding in the [terahertz](#) band."

More information: Xinrui Liu et al, Formation of gigahertz pulse train

by chirped terahertz pulses interference, *Scientific Reports* (2020). [DOI: 10.1038/s41598-020-66437-4](https://doi.org/10.1038/s41598-020-66437-4)

Provided by ITMO University

Citation: Scientists propose data encoding method for the 6G standard (2020, June 12) retrieved 20 September 2024 from <https://phys.org/news/2020-06-scientists-encoding-method-6g-standard.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.